

Certificate of Technical Specifications



PRODUCT: RESORT BE HARD
 FORMAT: 1000,0 X 1000,0 X 9,0 mm

CONTAINS: 2 Peças 2,00 m² 21,53 SQFT

GROUP: Bla

| Technical Characteristics | ISO | Req. | Unit | Specification |
|--|-----------|------------------|-------------------|---------------|
| DIM. VAR. IN REL. W. OF THE GREATER SIDE | 10545-2 | ±1,0 | mm | ±0,50 |
| DIM. VAR. IN REL. W. OF THE MINOR SIDE | 10545-2 | ±1,0 | mm | ±0,50 |
| THICKNESS VARIATION | 10545-2 | ±0,45 | mm | ±0,45 |
| STRAIGHTNESS OF THE GREATER SIDE | 10545-2 | ±0,80 | mm | ±0,80 |
| STRAIGHTNESS OF THE MINOR SIDE | 10545-2 | ±0,80 | mm | ±0,80 |
| DEVIATION FROM ORTHOGONALITY OF THE GREATER SIDE | 10545-2 | ±1,50 | mm | ±1,50 |
| DEVIATION FROM ORTHOGONALITY OF THE MINOR SIDE | 10545-2 | ±1,50 | mm | ±1,50 |
| CENTRAL DIAGONAL CURVATURE DEVIATION | 10545-2 | ±1,80 | mm | ±1,80 |
| DEVIATION OF THE CURVATURE OF THE SIDES | 10545-2 | ±1,80 | mm | ±1,80 |
| DEVIATION OF THE CURVATURE OF THE SIDES | 10545-2 | ±1,80 | mm | ±1,80 |
| BENDING OVER DIAGONAL | 10545-2 | ±1,80 | mm | ±1,80 |
| QUALITY OF SURFACE | 10545-2 | ≥95 | % | ≥95 |
| WATER ABSORPTION | 10545-3 | ≤0,50 | % | ≤0,50 |
| RESISTANCE TO BENDING | 10545-4 | ≥35 | N/mm ² | ≥35 |
| BREAKING STRENGTH | 10545-4 | ≥1300 | N | ≥1300 |
| CLASS OF USAGE | | Specify | USE | 6 |
| THERMAL SHOCK RESISTANCE | 10545-9 | - | - | - |
| LINEAR EXPANSION COEFFICIENT X 10-6 | 10545-8 | - | C-1 | - |
| MOISTURE EXPANSION | 10545-10 | - | mm/m | ≤0,30 |
| GRAZING RESISTANCE | 10545-11 | Required | - | OK |
| RESISTANCE TO CHEMICALS | 10545-13 | Minimum Class GB | - | GA |
| RESISTANCE ATTACKS ACID/ALKALINE | 10545-13 | Specify | - | GLB |
| SURFACE RESISTANCE TO STAINS | 10545-14 | Minimum Class 3 | - | 4 |
| COEFFICIENT OF FRICTION WET | NBR 16919 | Specify | | ≥0,6* |
| CHANGES IN HUE | | | | V3 |

Note: Product in accordance with the ABNT NBR 13006 standard

Evaluation of reaction to fire (NBR15575): Class I (non-combustible)

Class 6: All residential and commercial areas with heavy traffic.

*For products from March 2026 onward; between August 2022 and February 2026 consider friction ≥ 0.7; and for products prior to August 2022 consider friction ≥ 0.5.


 Andre Bez Batti
 Responsável Técnico