

Certificate of Technical Specifications



PRODUCT: MC PETIT POÁ WH LUX
FORMAT: 312X330X5,9 MM
CONTAINS: 5 Pieces 0.52 m² 5.59 SQFT
GROUP: Bla

Specifications	ISO	Demand.	Pcs.	Specification
DIM. VAR. IN REL. W. OF THE GREATER SIDE	10545-2	-	mm	-
DIM. VAR. IN REL. W. OF THE MINOR SIDE	10545-2	-	mm	-
THICKNESS VARIATION	10545-2	-	%	-
STRAIGHTNESS OF THE GREATER SIDE	10545-2	-	mm	-
STRAIGHTNESS OF THE MINOR SIDE	10545-2	-	mm	-
DEVIATION FROM ORTHOGONALITY OF THE GREATER SIDE	10545-2	-	mm	-
DEVIATION FROM ORTHOGONALITY OF THE MINOR SIDE	10545-2	-	mm	-
CENTRAL DIAGONAL CURVATURE DEVIATION	10545-2	-	mm	-
DEVIATION OF THE CURVATURE OF THE SIDES	10545-2	-	mm	-
DEVIATION OF THE CURVATURE OF THE SIDES	10545-2	-	mm	-
BENDING OVER DIAGONAL	10545-2	-	mm	-
QUALITY OF SURFACE	10545-2	-	%	≥95
WATER ABSORPTION	10545-3	-	%	≤0.50
RESISTANCE TO BENDING	10545-4	-	N/mm2	-
BREAKING STRENGTH	10545-4	-	N	-
CLASS OF USAGE		Specify	USE:	3
THERMAL SHOCK RESISTANCE	10545-9	-	-	-
LINEAR EXPANSION COEFFICIENT X 10-6	10545-8	-	C-1	-
MOISTURE EXPANSION	10545-10	-	mm/m	≤0.30
GRAZING RESISTANCE	10545-11	Required	-	OK
RESISTANCE TO CHEMICALS	10545-13	Min.Class GB	-	GA
RESISTANCE ATTACKS ACID/ALKALINE	10545-13	Specify	-	GLB
SURFACE RESISTANCE TO STAINS	10545-14	Min. Class 3	-	4
DYNAMIC COEFFICIENT OF FRICTION (DCOF)	NBR 16919	Specify		<0.4
CHANGES IN HUE				V2

Note: Product in compliance with ABNT NBR 13006 standard
Reaction to Fire Rating (NBR15575): Class I (non-combustible)
USE 3 - Use in residential premises without communication to the outside


Andre Bez Batti
Responsável Técnico