

Certificate of Technical Specifications

ceusa

PRODUCT: CALEIDOSCÓPIO HEX SGR NAT
 FORMAT: 174,4X174,4X7,4 MM

CONTAINS: 10 Pieces 0,26m² 2,80SQFT

GROUP: Bla

| Technical Characteristics | ISO | Req. | Unit | Specification |
|--|-----------|------------------|-------------------|---------------|
| DIM. VAR. IN REL. W. OF THE GREATER SIDE | 10545-2 | ±1.0 | mm | ±1.0 |
| DIM. VAR. IN REL. W. OF THE MINOR SIDE | 10545-2 | ±1.0 | mm | ±1.0 |
| THICKNESS VARIATION | 10545-2 | ±5.0 | % | ±5.0 |
| STRAIGHTNESS OF THE GREATER SIDE | 10545-2 | - | - | - |
| STRAIGHTNESS OF THE MINOR SIDE | 10545-2 | - | - | - |
| DEVIATION FROM ORTHOGONALITY OF THE GREATER SIDE | 10545-2 | - | - | - |
| DEVIATION FROM ORTHOGONALITY OF THE MINOR SIDE | 10545-2 | - | - | - |
| CENTRAL DIAGONAL CURVATURE DEVIATION | 10545-2 | - | - | - |
| DEVIATION OF THE CURVATURE OF THE SIDES | 10545-2 | - | - | - |
| DEVIATION OF THE CURVATURE OF THE SIDES | 10545-2 | - | - | - |
| BENDING OVER DIAGONAL | 10545-2 | - | - | - |
| QUALITY OF SURFACE | 10545-2 | ≥95 | % | ≥95 |
| WATER ABSORPTION | 10545-3 | ≤0.5 | % | ≤0.5 |
| RESISTANCE TO BENDING | 10545-4 | ≥35 | N/mm ² | ≥35 |
| BREAKING STRENGTH | 10545-4 | ≥700 | N | ≥700 |
| CLASS OF USAGE | 10545-7 | - | Use: | 5 |
| THERMAL SHOCK RESISTANCE | 10545-9 | - | - | - |
| LINEAR EXPANSION COEFFICIENT X 10-6 | 10545-8 | - | C-1 | - |
| MOISTURE EXPANSION | 10545-10 | - | mm/m | ≤0.30 |
| GRAZING RESISTANCE | 10545-11 | Required | - | OK |
| RESISTANCE TO CHEMICALS | 10545-13 | Minimum Class GB | - | GA |
| RESISTANCE ATTACKS ACID/ALKALINE | 10545-13 | Specify | - | GLB |
| SURFACE RESISTANCE TO STAINS | 10545-14 | Minimum Class 3 | - | 4 |
| COEFFICIENT OF FRICTION WET | NBR 16919 | Specify | - | ≥0.4 |
| CHANGES IN HUE | | | | V2 |

Note: Product in accordance with ABNT NBR 13006 standard

Reaction to fire evaluation (NBR15575): Class I (non-combustible)

USE 5 - All residential and commercial areas with moderate traffic.


 Jamilson Pinter Júnior
 Responsável Técnico RC1 e RC2


 Gildino da Luz
 Responsável Técnico RC3 e RC4